

AMENDMENTS TO THE CLAIMS

The following is a complete listing of all claims in the subject application with the status of each claim being indicated in a parenthetical expression. Currently amended claims are presented with markings indicating the changes that have been made relative to the immediate prior version.

1. (Currently Amended) A ~~compressible structure~~ window protection system for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and, said shaping member~~ defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure; and

a fluidic polymeric foam material for being introduced in said cavity , said fluidic material being capable of solidifying within said cavity into a body of shock absorbing compressible material providing shock absorbing protection for the glass pane.

2. (Previously Amended) A protected window structure comprising
a window structure including a frame circumscribing an area containing exposed glass having an exterior facing side;

a shaping member removably secured on said window structure and defining a cavity over said exterior facing side of said glass;

a body of solidified compressible material in said cavity of a size to cover said area circumscribed by said frame at least substantially in its entirety to provide protection for said glass, said compressible material being supplied to said cavity in a fluidic form and solidifying in said cavity; and

a port in said shaping member communicating with said cavity by which said compressible

material is supplied to said cavity in said fluidic form.

3. (Previously Amended) A protected window structure as recited in claim 2 wherein said compressible material is a polymeric foam.

4. (Currently Amended) A ~~compressible structure~~ window protection system as recited in claim 1 and further including a securing element for removably securing said ~~compressible structure~~ shaping member on the window structure.

5. (Currently Amended) A ~~compressible structure~~ window protection system as recited in claim 4 wherein said securing element includes a releasable adhesive carried by said shaping member.

6. (Currently Amended) A ~~compressible structure~~ window protection system as recited in claim 4 wherein said ~~compressible structure~~ shaping member has an external perimeter and said securing element includes one or more securing devices for being interposed between said perimeter and the window structure.

7. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and, said shaping member~~ defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure;

a layer of solidified compressible material in said cavity, said shaping member and said

solidified compressible material forming a compressible structure providing protection for the glass pane; and

a securing element for removably securing said compressible structure on the window structure, said securing element including one or more securing devices each including an attachment member and a clip, said attachment member having a planar base for being releasably, adhesively secured to the ~~glass pane~~ window structure and a pin extending perpendicularly from said base for penetrating said compressible structure so that a forward end of said pin protrudes from said compressible structure, said clip including an opening for receiving said forward end therethrough in releasable locking engagement to retain said compressible structure between said clip and said base.

8. (Currently Amended) A protected window structure as recited in claim 3 wherein said shaping member includes a front wall, a back wall disposed adjacent to the glass ~~pane~~ and one or more side walls connecting said front and back walls, said cavity being defined between said front and back walls.

9. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and~~, said shaping member defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure, said shaping member including a front wall, a back wall for being disposed adjacent the glass pane and one or more side walls connecting said front and back walls, said cavity being defined between said front and back walls, said back wall being made of a sponge material;

a layer of solidified compressible material in said cavity providing protection for the glass pane, said compressible material being a polymeric foam; and

a port in said shaping member communicating with said cavity by which said compressible material is supplied to said cavity in fluidic form ~~and solidifies~~ for solidification within said cavity.

10. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and~~, said shaping member defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure, said shaping member including a front wall, a back wall for being disposed adjacent the glass pane and one or more side walls connecting said front and back walls, said cavity being defined between said front and back walls, said back wall including spaced layers and a cushioning structure between said layers;

a layer of solidified compressible material in said cavity providing protection for the glass pane, said compressible material being a polymeric foam; and

a port in said shaping member communicating with said cavity by which said compressible material is supplied to said cavity in fluidic form ~~and solidifies~~ for solidification within said cavity.

11. (Previously Amended) A compressible structure as recited in claim 10 wherein said cushioning structure includes a plurality of air cells.

12. (Original) A compressible structure as recited in claim 10 wherein said cushioning structure includes a plurality of polymeric particles.

13. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and, said shaping member~~ defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure, said shaping member including a front wall, a back wall for being disposed adjacent the glass pane and one or more side walls connecting said front and back walls, said cavity being defined between said front and back walls;

a cushioning element carried by said back wall;

a layer of solidified compressible material in said cavity providing protection for the glass pane, said compressible material being a polymeric foam; and

a port in said shaping member communicating with said cavity by which said compressible material is supplied to said cavity in fluidic form ~~and solidifies~~ for solidification within said cavity.

14. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and, said shaping member~~ defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure, said shaping member including a front wall, a back wall for being disposed adjacent the glass pane and one or more side walls connecting said front and back walls, said cavity being defined between said front and back walls;

a layer of solidified compressible material in said cavity providing protection for the glass pane, said compressible material being a polymeric foam and being a releasably adherable material supplied to said cavity in fluidic form and thereafter solidifying;

a port in said shaping member communicating with said cavity by which said compressible material is supplied to said cavity in fluidic form ~~and solidifies~~ for solidification within said cavity;
and

an opening in said shaping member by which said compressible material in fluidic form

contacts the window structure to releasably adhere said shaping member to the window structure when said compressible material solidifies.

15. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and, said shaping member~~ defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure, said shaping member including a front wall, a back wall for being disposed adjacent the glass pane and one or more side walls connecting said front and back walls, said cavity being defined between said front and back walls, said front wall being made of a high strength, impact resistant material;

a layer of solidified compressible material in said cavity providing protection for the glass pane, said compressible material being a polymeric foam; and

a port in said shaping member communicating with said cavity by which said compressible material is supplied to said cavity in fluidic form ~~and solidifies~~ for solidification within said cavity.

16. (Currently Amended) A protected window structure comprising

a window structure having a glass pane mounted in a frame;

a shaping member removably secured on said window structure and defining a cavity over said glass pane, said shaping member including a front wall and one or more side walls extending rearwardly from said front wall to contact said window structure, said front wall being spaced from said glass pane by said one or more side walls, said cavity being defined between said front wall and said glass pane;

a layer of solidified compressible material in said cavity providing protection for said glass

pane, said compressible material being a polymeric foam; and

a port in said shaping member communicating with said cavity by which said compressible material is supplied to said cavity in fluidic form ~~and solidifies~~ for solidification within said cavity.

17. (Currently Amended) A compressible structure for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on the window structure ~~and~~, said shaping member defining a cavity disposed over the glass pane when said shaping member is removably secured on the window structure; and

a layer of solidified compressible material in said cavity providing protection for the glass pane, said layer of solidified compressible material including a first layer of a first solidified compressible material and a second layer of a second solidified compressible material disposed over said first layer, said first and second solidified compressible materials being of different densities.

18. (Original) A compressible structure as recited in claim 17 wherein said first solidified compressible material is of greater density than said second solidified compressible material.

19. (Original) A compressible structure as recited in claim 18 wherein said second layer of said second solidified compressible material is disposed between the glass pane and said first layer of said first solidified compressible material.

20. (Currently Amended) A ~~compressible~~ protected window structure as recited in claim 1 ~~2~~ wherein said body of ~~shock-absorbing~~ solidified compressible material has a thickness in the

range of 0.5 inch to 12.0 inches.

21. (Currently Amended) A ~~compressible~~ protected window structure as recited in claim 20 wherein said body of ~~shock-absorbing~~ solidified compressible material has a thickness in the range of 1.0 inch to 4.0 inches.

22. (Currently Amended) A ~~compressible structure~~ window protection system as recited in claim 1 wherein said shaping member is adjustable in external size in response to a variation in the amount of said fluidic material introduced in said cavity.

23. (Currently Amended) A ~~compressible structure~~ window protection system as recited in claim 1 and further comprising a port in said shaping member establishing communication with said cavity from externally of said shaping member and a delivery device for supplying said fluidic material through said port and into said cavity.

24. (Previously Canceled)

25. (Currently Amended) A ~~compressible~~ protected window structure as recited in claim 23 ~~2~~ and further including a securing element for removably securing said shaping member on said window structure.

26. (Currently Amended) A ~~compressible~~ protected window structure as recited in claim 25 wherein said securing element includes an adhesive.

27. (Currently Amended) A ~~compressible~~ protected window structure as recited in claim 25 wherein said securing element includes one or more mechanical securing devices.

28. (Currently Amended) A window protection system for temporarily protecting a glass pane of a window structure comprising

a shaping member for removable securement on a window structure ~~and, said shaping member~~ defining a cavity disposed over the glass pane when said shaping member is removably secured on the window;

a port in said shaping member establishing communication with said cavity from externally of said shaping member; and

a supply system including a quantity of compressible material in fluid form and a delivery device for supplying said compressible material in fluid form through said port and into said cavity, said compressible material in fluid form solidifying within said cavity to form a layer of solidified compressible material thereby forming a compressible structure, defined by said shaping member and said layer of solidified compressible material, over the glass pane to provide protection thereto, said quantity of compressible material in fluid form including a quantity of a first compressible material in fluid form for forming a first layer of a first solidified compressible material having a first density and a quantity of a second compressible material in fluid form for forming a second layer of a second compressible material having a second density greater than said first density.

29. (Previously Amended) A temporarily protected window structure comprising
a window structure having a glass pane mounted in a frame; and
a compressible structure removably secured on said window structure and including a panel of solidified compressible foam material disposed over the exterior of said glass pane with said

panel having a thickness extending perpendicular to said glass pane, said thickness being compressible and said compressible material having a compression strength in the range of 15 to 40 psi to protect said glass pane from damage due to storms.

30. (Previously Amended) A protected window structure as recited in claim 29 and further including a securing element removably securing said compressible structure on said window structure.

31. (Original) A protected window structure as recited in claim 30 wherein said securing element includes an adhesive.

32. (Original) A protected window structure as recited in claim 30 wherein said securing element includes one or more mechanical securing devices.

33. (Original) A protected window structure as recited in claim 32 wherein said compressible structure has an external perimeter and said one or more securing devices are interposed between said perimeter and said window structure.

34. (Currently Amended) A temporarily protected window structure comprising
a window structure having a glass pane mounted in a frame;
a compressible structure removably secured on said window structure and including a panel of solidified compressible foam material disposed over said glass pane to protect said glass pane from damage due to storms; and
a securing element removably securing said compressible structure on said window

structure, said securing element including one or more mechanical securing devices, said one or more securing devices each including an attachment member and a clip, said attachment member having a planar base releasably, adhesively secured to said ~~glass pane~~ window structure and a pin extending perpendicularly from said base for penetrating said compressible structure so that a forward end of said pin protrudes from said compressible structure, said clip including an opening for receiving said forward end therethrough in locking engagement to retain said compressible structure between said clip and said base.

35. (Previously Amended) A temporarily protected window structure comprising a window structure having a glass pane mounted in a frame;
a compressible structure removably secured on said window structure and including a panel of solidified compressible foam material disposed over said glass pane to protect said glass pane from damage due to storms, said panel of solidified compressible material including a first layer of a first solidified compressible material having a first density and a second layer of a second solidified compressible material disposed over said first layer and having a second density greater than said first density; and
a securing element removably securing said compressible structure on said window structure.

36. (Original) A protected window structure as recited in claim 35 wherein said first layer is disposed between said second layer and said glass pane.

37. (Previously Amended) A method of temporarily protecting a glass pane of a window structure in a building from storm damage, comprising the steps of

before a storm arrives, releasably securing a pre-formed panel of solidified compressible foam material over the exterior of the glass pane with the thickness of the panel perpendicular to the glass pane;

leaving the panel in place during the storm;

compressing the thickness of the panel in response to objects forcefully striking the panel during the storm to protect the glass pane from damage; and

after the storm has passed, removing the panel from the glass pane.

38. (Original) A method of temporarily protecting a glass pane as recited in claim 37 wherein said step of releasably securing includes adhesively securing the panel to the glass pane.

39. (Original) A method of temporarily protecting a glass pane as recited in claim 37 wherein said step of releasably securing includes positioning one or more securing devices between the window structure and an external perimeter of the panel.

40. (Previously Amended) A method of temporarily protecting a glass pane of a window structure in a building from storm damage, comprising the steps of

before a storm arrives, releasably securing a pre-formed panel of solidified compressible material over the glass pane, said step of releasably securing including the steps of inserting a pin of an attachment member through the panel so that a base of the attachment member abuts a back surface of the panel and a forward end of the pin protrudes from a forward surface of the panel, positioning a clip on the forward end of the pin to releasably, lockingly retain the panel between the clip and the base, and releasably attaching the base to the window structure;

leaving the panel in place during the storm to protect the glass pane from damage; and
after the storm has passed, removing the panel from the glass pane.

41. (Original) A method of temporarily protecting a glass pane as recited in claim
40 wherein said step of releasably attaching includes releasably attaching the base to the window
structure adhesively.

42. (Original) The method of temporarily protecting a glass pane as recited in claim
37 and further including, subsequent to said step of removing, the step of storing the panel for
reuse.

43. (Original) A method of temporarily protecting a glass pane of a window structure
in a building from storm damage, comprising the steps of
before a storm arrives, removably securing a shaping member on the window structure so
that a cavity defined by the shaping member is disposed over at least a portion
of the glass pane;

supplying a fluidic compressible material to the cavity;

allowing the fluidic compressible material to cure and form a layer of solidified compressible
material thereby forming a compressible structure over at least a portion of the glass pane;

leaving the compressible structure in place during the storm to protect the window structure
from damage; and

after the storm has passed, removing the compressible structure from the window structure.

44. (Currently Amended) A ~~compressible structure~~ window protection system as recited

in claim 1 wherein said fluidic material is capable of solidifying into a body of compressible material ~~includes~~ including cells in the size range of 0.005mm to 5.0mm.

45. (Previously New) A protected window structure as recited in claim 2 wherein said exposed glass includes one or more glass panes.

46. (Previously New) A protected window structure as recited in claim 2 wherein said body of solidified compressible material covers the entirety of said area circumscribed by said frame.